

Features

EASILY CONFIGURED TO MEET YOUR NEEDS

FORK OPTIONS

- Standard forks
- Load platform
- Boom

POWER OPTIONS

- Standard winch
- Electric winch

BASE OPTIONS

- Standard base (GL-4, -8 only)
- Straddle base (all units)
- Counterweight base (GL-4, -8, -10 only)

WHEEL/CASTER OPTIONS

Straddle and standard base

- 8 in (20 cm) non-marking rear wheels
- Pneumatic rear tire option
- 2 in (5 cm) dual wheel front swivel casters

Counterweight base

- 5 in (12 cm) rear swivel casters with side brakes
- 4 in (10 cm) fixed front wheels

Straddle base

- 4 point caster option

STANDARD FEATURES

MEASUREMENTS

GL™-4

- 5 ft 11 in (1.80 m) maximum lift height
- Up to 500 lb (227 kg) load capacity

GL™-8

- 10 ft .5 in (3.06 m) maximum lift height
- Up to 400 lb (181 kg) load capacity

GL™-10

- 11 ft 8 in (3.56 m) maximum lift height
- Up to 350 lb (159 kg) load capacity

GL™-12

- 13 ft 9.5 in (4.20 m) maximum lift height
- Up to 350 lb (159 kg) load capacity

PRODUCTIVITY

- Portable and compact design
- Lightweight durable aluminum construction
- Single door access
- Durable standard steel forks
- 8 in (20 cm) non-marking rear wheels and 2 in (5 cm) dual wheel front swivel casters (standard and straddle base only)
- 5 in (12 cm) rear swivel casters with side brakes and 4 in (10 cm) fixed front wheels (counterweight base only)
- Loads easily into a pickup truck for transporting
- Hold-down mechanism secures carriage during transport

POWER

- Standard winch
- Reversible winch handle for easy storage



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Load platform
- Boom
- Aluminum ladder (standard and straddle base only)
- Pneumatic rear tires (standard and straddle base only)
- Foot-release brake (standard and straddle base only)
- Caster options
- Stair rollers (standard base only)

POWER

- Electric winch (straddle and counterweight base only)
- Winch operates while ladder is in use or stowed
- Caster option kit required for use with Straddle bases
- Electric winch option comes standard with battery and automatic charger that shuts off when fully charged.

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730

Telephone **(425) 881-1800**
Toll Free in USA/Canada **800-536-1800**
Fax (425) 883-3475

Genie Europe

The Maltings
Wharf Road
Grantham NG31 6BH
U.K.

Telephone **+44 (0)1476 584333**
Fax +44 (0)1476 584334

Email: infoeurope@genieind.com

Distributed By:

For further information, please contact your local distributor or the Genie Industries sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. Genie makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of TEREX Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. Copyright © 2006 Genie Industries, Inc. "Genie" is a Registered Trademark of Genie Industries, Inc. in the USA and many other countries. Genie is a TEREX Company.